

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA  
GHS

Printing date: 03 July 2018

Revision: 03 July 2018

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name: **Rapid Remover**

Other means of identification: No other identifiers

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture: Surface cleaning

Uses advised against: No further relevant information available.

### 1.3 Details of the supplier of the Safety Data Sheet

#### Manufacturer/Supplier:

Rapid Tac  
186 Combs Dr.  
Merlin, OR 97532  
Phone: (541) 474-1113  
Email: mail@rapidtac.com

### 1.4 Emergency telephone number:

ChemTel Inc.  
(800)255-3924 (North America)  
+1 (813)248-0585 (International)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008

Classifications listed are applicable to the OSHA GHS Hazard Communication Standard (29CFR1910.1200).

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H400, H410.

Flam. Liq. 3	H226	Flammable liquid and vapour.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.
Aquatic Acute 1	H400	Very toxic to aquatic life.
Aquatic Chronic 1	H410	Very toxic to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the Globally Harmonized System within the United States.

The product is classified and labelled according to the CLP regulation.

#### Hazard pictograms

The following pictogram(s) are only for use within Europe: GHS09.

(Cont'd. on page 2)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA  
GHS

Printing date: 03 July 2018

Revision: 03 July 2018

**Trade name: Rapid Remover**

(Cont'd. from page 1)



GHS02 GHS07 GHS08 GHS09

- **Signal word** Danger
  - **Hazard-determining components of labelling:**  
Distillates (petroleum), hydrotreated light  
(R)-p-mentha-1,8-diene
  - **Hazard statements**  
The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H410.  
H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H304 May be fatal if swallowed and enters airways.  
H410 Very toxic to aquatic life with long lasting effects.
  - **Precautionary statements**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing mist/vapours/spray.  
P280 Wear protective gloves / eye protection.  
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P331 Do NOT induce vomiting.  
P302+P352 IF ON SKIN: Wash with plenty of water.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- 
- **2.3 Other hazards** There are no other hazards not otherwise classified that have been identified.
  - **Results of PBT and vPvB assessment**
  - **PBT:** Not applicable.
  - **vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

### · 3.2 Mixtures

#### · Components:

CAS: 64742-47-8 EINECS: 265-149-8 Index number: 649-422-00-2 Reg.nr.: 01-2119484819-18-XXXX	Distillates (petroleum), hydrotreated light ----- Asp. Tox. 1, H304	25-50%
CAS: 5989-27-5 EINECS: 227-813-5 Index number: 601-029-00-7	(R)-p-mentha-1,8-diene ----- Flam. Liq. 3, H226 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	10-25%

(Cont'd. on page 3)